

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Mar 2023

Print date: 20 Mar 2023

Version: 0.3



Page 1/11

REDOCOL Wood Filler Dilution

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

REDOCOL Wood Filler Dilution

Article No.:

HK10002

Index No.:

505-001-00-8

CAS No.:

67-64-1

EC No.:

200-662-2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Solvent

Relevant identified uses:

Sector of uses [SU]

SU 0: Other

Product Categories [PC]

PC 0: Other

Article categories [AC]

AC 1: Vehicles

1.3. Details of the supplier of the safety data sheet

distributor:

Ostermann UK Ltd

Stonebridge Cross Business Park

Unit 104 Pointon Way

WR9 0LW Droitwich

United Kingdom

Telephone: UK +44 (0) 1905 793 550, Ireland +44 (0) 1905 793 552

Telefax: +44 (0) 1905 793 559

E-mail: UK sales.uk@ostermann.eu, Ireland sales.ie@ostermann.eu

Website: www.ostermann.eu

E-mail (competent person): j.bruns@ostermann.eu

1.4. Emergency telephone number

UK: Mr. J. Bruns +44 1905 793 550

IR: Mr. J. Bruns +44 1905 793 552, 24h: +49 30 - 30 68 67 00 (National Poison Inform. Centre Berlin) , UK +44 1905 793 550/ IR +44 (0)1905 793 552 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Mar 2023

Print date: 20 Mar 2023

Version: 0.3



Page 2/11

REDOCOL Wood Filler Dilution

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS07
Exclamation mark

Signal word: Danger

Hazard statements for physical hazards

H225	Highly flammable liquid and vapour.
------	-------------------------------------

Hazard statements for health hazards

H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Supplemental hazard information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Precautionary statements Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements Response

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/First aider if you feel unwell.
P337 + P313	If eye irritation persists: Get medical advice/attention.

Precautionary statements Storage

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
-------------	--

Precautionary statements Disposal

P501	Dispose of contents/container to Disposal methods.
------	--

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 67-64-1 EC No.: 200-662-2 Index No.: 606-001-00-8 REACH No.: 01-2119471330-49	acetone Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066	70 - < 100 weight-%

Full text of H- and EUH-phrases: see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Mar 2023

Print date: 20 Mar 2023

Version: 0.3



Page 3/11

REDOCOL Wood Filler Dilution

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Remove casualty to fresh air and keep warm and at rest. If unconscious but breathing normally, place in recovery position and seek medical advice.

Following inhalation:

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. Rub greasy ointment into the skin. In case of skin irritation, consult a physician.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. In case of eye irritation consult an ophthalmologist.

Following ingestion:

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Water, to which activated charcoal may be added
IF SWALLOWED: Immediately call a doctor.

Self-protection of the first aider:

No direct artificial respiration to be given by first aider.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Subsequent observance for pneumonia and lung oedema. If breathing is irregular or stopped, administer artificial respiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use sand, extinguishing powder or alcohol resistant foam. Carbon dioxide (CO₂), Water spray jet.

Unsuitable extinguishing media:

Full water jet.

5.2. Special hazards arising from the substance or mixture

Highly flammable Vapours can form explosive mixtures with air. Beware of reignition. In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. [Use ... to extinguish].

Hazardous combustion products:

In case of fire may be liberated: Carbon dioxide Carbon monoxide.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Heating causes rise in pressure with risk of bursting. Cool endangered containers by spraying with water. Move undamaged containers from immediate hazard area if it can be done safely. Do not allow run-off from fire-fighting to enter drains or water courses. Appropriate disposal / Product Temperature Class: T1 (DIN 57165), Dust explosive, Dust explosion category: ST 2: II A (DIN 57165), Fire class: B. Flash point (°C) :4% Acetone + 96% Water = 54 °C.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Remove persons to safety.

Protective equipment:

Use personal protection equipment.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Mar 2023

Print date: 20 Mar 2023

Version: 0.3



Page 4/11

REDOCOL Wood Filler Dilution

6.1.2. For emergency responders

Personal protection equipment:

Wear a self-contained breathing apparatus and chemical protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment:

Methods and materials for containment and cleaning up Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:

Clean with detergents. Avoid solvent cleaners.

Other information:

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Dilute with plenty of water. Highly flammable

6.4. Reference to other sections

SECTION 8: Exposure controls/personal protection SECTION 13: Disposal considerations

6.5. Additional information

not applicable

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Technical ventilation of workplace, Carry out filling operations only at stations with exhaust ventilation facilities. Risk of explosion if heated under confinement. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. none AIR, COMPRESSED. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/ electrical equipment).

Packaging materials:

Keep only in the original container in a cool, well-ventilated place away from highly flammable substances. Keep container tightly closed in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)". Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Stainless steel, Only use containers specifically approved for the substance/product.

Hints on storage assembly:

Do not store together with:

Combustible substances of acute toxicity, category 3 / hazardous substances that are toxic or produce chronic effects

Non-combustible substances of acute toxicity, category 3 / hazardous substances that are toxic or produce chronic effects

Combustible substances of acute toxicity, category 1 and 2 / very toxic substances

Non-combustible substances of acute toxicity, category 1 and 2 / very toxic substances

May form explosive peroxides.

Storage class (TRGS 510, Germany): 3 - Flammable liquids

7.3. Specific end use(s)

Industrial sector specific solutions:

Water-based surface treatment agents, solvent-free

GISCODE:

W1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Mar 2023

Print date: 20 Mar 2023

Version: 0.3



Page 5/11

REDOCOL Wood Filler Dilution

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
IE	acetone CAS No.: 67-64-1 EC No.: 200-662-2	① 500 ppm (1,210 mg/m ³) ⑤ IOELV
IOELV (EU)	acetone CAS No.: 67-64-1 EC No.: 200-662-2	① 500 ppm (1,210 mg/m ³)
WEL (GB)	acetone CAS No.: 67-64-1 EC No.: 200-662-2	① 500 ppm (1,210 mg/m ³) ② 1,500 ppm (3,620 mg/m ³)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
acetone CAS No.: 67-64-1 EC No.: 200-662-2	1,210 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	200 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	2,420 mg/m ³	① DNEL worker ② Acute - inhalation, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	186 mg/kg	① DNEL worker ② Long-term - dermal, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	62 mg/kg	① DNEL Consumer ② Long-term - dermal, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	62 mg/kg	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
acetone CAS No.: 67-64-1 EC No.: 200-662-2	10.6 mg/L	① PNEC aquatic, freshwater
acetone CAS No.: 67-64-1 EC No.: 200-662-2	1.06 mg/L	① PNEC aquatic, marine water
acetone CAS No.: 67-64-1 EC No.: 200-662-2	100 mg/L	① PNEC sewage treatment plant
acetone CAS No.: 67-64-1 EC No.: 200-662-2	30.4 mg/kg	① PNEC sediment, freshwater
acetone CAS No.: 67-64-1 EC No.: 200-662-2	3.04 mg/kg	① PNEC sediment, marine water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Mar 2023

Print date: 20 Mar 2023

Version: 0.3



Page 6/11

REDOCOL Wood Filler Dilution

Substance name	PNEC Value	① PNEC type
acetone CAS No.: 67-64-1 EC No.: 200-662-2	21 mg/L	① PNEC aquatic, intermittent release
acetone CAS No.: 67-64-1 EC No.: 200-662-2	29.5 mg/kg	① PNEC soil, freshwater

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

8.2.2. Personal protection equipment



Eye/face protection:

The product will be applied by spraying. Wear eye/face protection. (EN 166)

Skin protection:

Butyl caoutchouc (butyl rubber) (Level 6, Breakthrough time: >480 min.), CHLOROPRENE, STABILIZED (Level 1, Breakthrough time: > 10 min.)

Respiratory protection:

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Thermal hazards:

Take precautionary measures against static discharges.

Other protection measures:

Wash hands before breaks and after work. After cleaning apply high-fat content skin care cream. When using do not eat, drink, smoke, sniff. Wear protective gloves/protective clothing/eye protection/face protection.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: colourless

Odour: Acetone

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	5 - 6		① 10g/L: neutral, 50% in H ₂ O: 5-6 ② MSDS Distributor
Melting point	-94.7 °C		② MSDS Distributor
Freezing point	<i>not determined</i>		
Initial boiling point and boiling range	56.05 °C		② MSDS Distributor
Decomposition temperature	<i>not determined</i>		
Flash point	-17 °C		② MSDS Distributor
Evaporation rate	<i>not determined</i>		
Auto-ignition temperature	465 °C		② MSDS Distributor
Upper/lower flammability or explosive limits	2.5 - 14.3 Vol-%		② MSDS Distributor

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Mar 2023

Print date: 20 Mar 2023

Version: 0.3



Page 7/11

REDOCOL Wood Filler Dilution

Parameter	Value	at °C	① Method ② Remark
Vapour pressure	240 hPa	20 °C	② MSDS Distributor
Vapour density	<i>not determined</i>		
Density	79 g/mL	20 °C	② MSDS Distributor
Relative density	<i>not determined</i>		
Bulk density	<i>not determined</i>		
Water solubility	very soluble	20 °C	② MSDS Distributor
Partition coefficient: n-octanol/water	<i>not determined</i>		
Dynamic viscosity	0.32 mPa*s	20 °C	② MSDS Distributor
Kinematic viscosity	<i>not determined</i>		
Odour threshold:	47.5 mg/m ³		② MSDS Distributor

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

other bases.

10.2. Chemical stability

Vapours can form explosive mixtures with air. Flammable gases.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

plastic and rubber, barium Sodium and potassium hydroxide: Condensation.

10.6. Hazardous decomposition products

Carbon monoxide, Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

acetone CAS No.: 67-64-1 EC No.: 200-662-2

LD₅₀ oral: 5,800 mg/kg (Rat) Journal of Toxicology and Environmental Health. Vol. 15, Pg. 609, 1985.

LD₅₀ dermal: >7,426 mg/kg (Rabbit)

LC₅₀ Acute inhalation toxicity (vapour): 50.1 mg/L (Rat) Am Ind Hyg Assoc J 20: 364-369

Acute oral toxicity:

Gastrointestinal complaints

Acute inhalation toxicity:

Vapours may cause drowsiness and dizziness. (>1000 ppmvapour)

Skin corrosion/irritation:

Irritant — skin irritation and eye damage Repeated exposure may cause skin dryness or cracking.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Serious eye damage/irritation:

Irritant — skin irritation and eye damage

Carcinogenicity:

No indication of human carcinogenicity.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Mar 2023

Print date: 20 Mar 2023

Version: 0.3



Page 8/11

REDOCOL Wood Filler Dilution

Reproductive toxicity:

none Toxic for reproduction.

11.2. Information on other hazards

No data available

SECTION 12: Ecological information

12.1. Toxicity

acetone CAS No.: 67-64-1 EC No.: 200-662-2

LC₅₀: 4,350 - 11,000 mg/L 4 d (fish, Pimephales promelas (fathead minnow)) OECD Guideline 203 (Fish, Acute Toxicity Test)

LC₅₀: 10 - 30,600 mg/L 2 d (crustaceans, Daphnia pulex (water flea)) Cowgill, U.M., and D.P. Milazzo 1991. The Sensitivity of Ceriodaphnia dubia and Daphnia magna to Seven Chemicals Utilizing the Three-Brood Test. Arch. Environ. Contam. Toxicol. 20(2):211-217; Canton, J.H., and D.M.M. Adema 1978. Reproducibility of Short-Term and Reproduction Toxicity Experiments with Daphnia magna and Comparison of the Sensitivity of Daphnia magna with Daphnia pulex and Daphnia cucullata in Short-Term Experiments. Hydrobiologia 59(2):135-140 (Used Reference 2018)

EC₅₀: 13,500 - 23,500 mg/L 2 d (crustaceans) Randall, T.L., and P.V. Knopp 1980. Detoxification of Specific Organic Substances by Wet Oxidation. J. Water Pollut. Control Fed. 52(8):2117-2130; Barera, Y., and W.J. Adams 1983. Resolving Some Practical Questions About Daphnia Acute Toxicity Tests. In: W.E. Bishop (Ed.), Aquatic Toxicology and Hazard Assessment, 6th Symposium, ASTM STP 802, Philadelphia, PA :509-518

EC₅₀: 7,200 - 7,200 mg/L 4 d (Algae/water plant, Microcystis aeruginosa) Slooff, W. 1982. A Comparative Study on the Short-Term Effects of 15 Chemicals on Fresh Water Organisms of Different Tropic Levels. Natl. Tech. Inf. Serv., Springfield, VA :25 p. (DUT) (ENG ABS) (NTIS/PB83-200386)

12.2. Persistence and degradability

acetone CAS No.: 67-64-1 EC No.: 200-662-2

Biodegradation: Yes, rapidly

Abiotic degradation:

DT50, 19-114d (air) none (Water, Hydrolysis)

Biodegradation:

91%/28d (OECD 301B)

Additional information:

Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

acetone CAS No.: 67-64-1 EC No.: 200-662-2

Log K_{ow}: -0.24

Bioconcentration factor (BCF): 3

12.4. Mobility in soil

Henry's Law Constant: 2,929-3,070 Pa*m³/mol (25 °C Water), Henry's Law Constant: 3,311 Pa*m³/mol (25 °C aquatic, marine water).

12.5. Results of PBT and vPvB assessment

acetone CAS No.: 67-64-1 EC No.: 200-662-2

Results of PBT and vPvB assessment: —

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste codes/waste designations according to EWC/AVV

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Mar 2023

Print date: 20 Mar 2023

Version: 0.3



Page 9/11

REDOCOL Wood Filler Dilution

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

14 06 03 *	other solvents and solvent mixtures
------------	-------------------------------------

*: Evidence for disposal must be provided.

Waste code packaging

15 01 05	composite packaging
----------	---------------------

Waste treatment options

Appropriate disposal / Product:

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Appropriate disposal / Package:

Non-contaminated packages may be recycled.

Other disposal recommendations:

Return to Distributor..

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1090	UN 1090	UN 1090	UN 1090
14.2. UN proper shipping name			
ACETONE (Acetone)	ACETONE (Acetone)	ACETONE (Acetone)	ACETONE
14.3. Transport hazard class(es)			
 3	 3	 3	 3
14.4. Packing group			
II	II	II	
14.5. Environmental hazards			
	No data available	No data available	No data available
14.6. Special precautions for user			
Special Provisions: MP19 Limited quantity (LQ): LQ4 1L Excepted Quantities (EQ): E2 Hazard identification number (Kemler No.): 33 Classification code: F1 Tunnel restriction code: (D/E)	Limited quantity (LQ): LQ - 1L Excepted Quantities (EQ): E2 Classification code: F1	Limited quantity (LQ): 1L Excepted Quantities (EQ): E2 EmS-No.: F-E; S-D	Excepted Quantities (EQ): E2

14.7. Maritime transport in bulk according to IMO instruments

No data available.

Additional information:

Portable tanks/vessels. T4, TP1, LGBF

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Mar 2023

Print date: 20 Mar 2023

Version: 0.3



Page 10/11

REDOCOL Wood Filler Dilution

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations (EU):

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive], Hazard categories:

- P5a Flammable Liquids, Category 1 or 2
- P5b Flammable liquids
- P5c Flammable liquids of Categories 2 or 3, not covered by P5a and P5b

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 100 weight-%

15.1.2. National regulations

[GB] National regulations

Other regulations, restrictions and prohibition regulations

Hazchem DG-EA-Code: 2YE

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has been carried out.

15.3. Additional information

Hazard categories: A, HA, Protective measures 2

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

AC	Article Category
ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM	American Society for Testing and Materials
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DIN	German Institute for Standardization / German Industrial Standard
DNEL	derived no-effect level
EC ₅₀	Effective Concentration 50%
ECHA	European Chemicals Agency
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
OECD	Organisation for Economic Cooperation and Development

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Mar 2023

Print date: 20 Mar 2023

Version: 0.3



Page 11/11

REDOCOL Wood Filler Dilution

OEL	Threshold Limit Value
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PC	Product category
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
STP	sewage treatment plant
SU	use category
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
VOC	Volatile organic compounds
ZNS	central nervous system

For abbreviations and acronyms, see ECHA: Guidance on information requirements and chemical safety assessment, Chapter R.20 (list of terms and abbreviations).

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6. Training advice

No data available

16.7. Additional information

No data available