

# MS-POLYMER 660.01/02/05/09

REDOCOL MS-Polymer 660.01/02/05/09 is a ready-to-use, high-quality assembly glue based on MS-Polymer. REDOCOL MS-Polymer 660.01/02/05/09 is suitable for sealing joints as well. The adhesive can be painted over, stays elastic and has a high initial strength.

- Suitable for a number of materials
- Bonding and sealing at the same time
- High initial tack
- Waterproof
- Stays elastic
- Can be painted over
- Colourfast
- Solvent-free
- Available colours: white, transparent, grey, black

## Application areas

Suitable for bonding nearly all materials like (natural) stone, concrete, mirrors, cement, PVC, various plastics, metal, aluminium, copper, lead, zinc, wood, glass and compact boards. Suitable as water-resistant sealant.

## Application

Surfaces for bonding must be clean, dust- and grease-free. Apply REDOCOL MS-Polymer 660.01/02/05/09 and press shortly. Distribute the glue and fix the parts, if needed. Processing is usually possible with standard cartridge guns.

Min. processing temperature:	+5° C
Temperature resistance:	-40° C bis +90° C
Open time:	10 min.
Cure time:	24 h
Skin building time:	approx. 10 min

## Shelf life

In closed condition, REDOCOL MS-Polymer 660.01/02/05/09 lasts for 12 months. The adhesive should be stored in a cool and frostfree place.

## Packaging

Cartridges with a content of 290 ml.

**Please note the safety data sheet!**