

FSG COOLING AGENT, TYPE KM 1 PLUS

Uses

For spraying onto the edges of furniture after applying plastic or wood veneer edgings.

Product Features

- The sprayed-on cooling agent, type KM 1 Plus, statically discharges the edging and cools the glue joint at the same time.
- sensing rollers and workpieces remain free of milling chips
- glue hardens faster

Processing Information

- Fill the tank of the spray nozzle with refrigerant, type KM 1 Plus, and set the optimum spraying strength.
- Adjust the spray setting as required.

Product Data

Physical state: liquid

Colour: bluish

Odour: paraffin

Shelf life: 2 - 3 years

Safety Instructions

- highly flammable liquid and vapour
- causes serious eye irritation
- Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition. Do not smoke.
- Take measures against electrostatic discharges.
- Wear protective gloves / protective clothing / eye protection / face protection
- IF IN EYES: rinse cautiously with water for several minutes. Remove any contact lenses if possible. Continue rinsing.
- If eye irritation persists: seek medical advice / medical attention-

Extract from the law. For further information see Safety Data Sheet.

Disposal Instructions

- Do not allow material to enter sewage system.
- Return empty containers to the manufacturer or drain and vent them completely and recycle them.
- For more information, see Safety Data Sheet or ask your local waste management office.

Delivery Form

| | |
|------|------------------|
| 1 l | bottle |
| 5 l | plastic canister |
| 30 l | plastic canister |